

# Clickeze Privacy and Shower Curtain Specification

## PART 1 GENERAL

### 1.01 SUMMARY

- A. Cubicle Curtain
- B. Shower Curtain

### 1.02 SECTIONS INCLUDES

- A. Curtains

### 1.03 REFERENCES

- A. National Fire Protection Association (NFPA)

### 1.04 SYSTEM DESCRIPTION

- A. Performance Requirements: Provide curtains that conform to the following requirements of regulatory agencies and the quality control of Clickeze, InPro Corporation.
  - 1. Fire Performance Characteristics: Provide curtains that are fire retardant or fire resistant.

### 1.05 SUBMITTALS

- A. Product Data: Manufacturer's printed product data for each type of curtain specified.
- B. Fabric Samples: Swatch cards of fabric samples illustrating fabric color and weave.
- C. Manufacturer's Care Instructions: Printed care instructions for each curtain.

### 1.06 DELIVERY, STORAGE AND HANDLING

- A. Deliver materials in unopened factory packaging to the jobsite.
- B. Inspect materials at delivery to assure that specified products have been received.
- C. Store in original packaging in a climate controlled location away from direct sunlight.

### 1.07 PROJECT CONDITIONS

- A. Environmental Requirements: Products must be installed in an interior climate controlled environment.

### 1.08 WARRANTY

A. Standard Clickeze Limited Lifetime Warranty against material and manufacturing defects.

## PART 2 – PRODUCTS

### 2.01 MANUFACTURER

A. Acceptable Manufacturer Clickeze, InPro Corp.

PO Box 406 Muskego, WI 53150 USA

Telephone: 800-222-5556

Fax: 888-715-8407, [www.inprocorp.com](http://www.inprocorp.com)

B. Substitutions: Not permitted

C. Provide all privacy curtains from a single source.

### 2.02 MATERIALS

A. Privacy Curtain

1. Fabric: Provide 100% polyester curtains. Fabric is to be opaque, washable, flame retardant and closely woven.

2. Shield Fabric: Provide 100% polyester, impregnated and multi-coated with Aqueous based microporous polymers.

3. Open Mesh Cloth: Provide curtain heading of open weave nylon mesh material with 1/2" holes to permit air and steam circulation. Mesh is to be flame retardant, washable and dry-cleanable.

B. Shower Curtain

1. Vinyl Material: Provide heavy duty, 8 gauge, flame retardant, anti-microbial vinyl that is water repellent, wear resistant, scrubbable and colorfast.

2. Fabric: Provide 100% polyester or polyester/cotton blend curtains. Fabric is to be washable and closely woven.

3. Shield Fabric: Provide 100% polyester, impregnated and multi-coated with Aqueous based microporous polymers.

4. Open Mesh Cloth: Provide curtain heading of open weave nylon mesh material with 1/2" holes to permit air and steam circulation. Mesh is to be flame retardant, washable and dry-cleanable.

### 2.03 FINISH AND COLOR

A. Privacy Curtain Fabric: Select solid or patterned fabric from manufacturer's standard selection.

B. Shower Curtain Vinyl: Select solid or patterned opaque material or light transmitting vinyl from manufacturer's standard selection.

C. Open Mesh Cloth: Provide curtain heading of mesh material in a color selected from manufacturer's

standard selection.

## 2.04 FABRICATION

### A. Curtain

1. Curtain Width: Manufacture curtains of one piece, sized to 10 percent wider than the track length but no less than 1 foot extra fullness.

2. Curtain Height: Specify height. Bottom of privacy curtains hang 12" – 15" above floor. Dressing room curtains hang 4" – 6" above floor. Shower curtains hang 1" above floor. Tub curtains hang 6" above floor.

3. Curtain Heading: Manufacture with or without heading of open mesh cloth, to the same width as the curtain fabric. Include 4-ounce nickel-plated grommets, 6" on center for carriers. Shower curtain top hem to be triple-turned hem over nylon tape for rugged wear.

### 4. Seams

a. Privacy Curtain: Bottom hem shall be double-fold and 1 1/4" wide. Curtains shall be seamless if possible or lock stitch seams in two rows. Turn seam edges and lock stitch. Sewing thread to be triple-ply twisted nylon.

b. Shower Curtain: Curtains are to be seamless when possible with sanitary "no scum" side and bottom edges. Sewing thread to be triple ply twisted nylon.

## PART 3 – EXECUTION

### 3.01 EXAMINATION

A. Examine areas and conditions in which privacy tracking system will be installed.

1. Complete all finishing operations, including painting, before beginning installation of privacy tracking system materials.

2. Verify that surfaces and above ceiling supports are ready to receive work.

### 3.02 PREPARATION

A. General: Prior to installation, clean substrate to remove dust, debris and loose particles.

### 3.03 INSTALLATION

A. General: Locate the privacy track as indicated on the approved detail drawing for the appropriate substrate and in compliance with the Clickeze installation instructions.

B. Installation of Privacy Tracking Systems:

1. Install privacy track, secure, rigid, and true to ceiling line.
2. Slide carriers onto the track.
3. Install end cap or stop device.
4. Secure or suspend track to ceiling system. Install with mechanical fasteners or Gridclips.
5. Install curtains on carriers ensuring smooth operation.

### 3.04 CLEANING

A. At completion of the installation, remove any debris and clean surfaces in accordance with the clickeze clean-up and maintenance instructions.